

The award winning S38 water conditioner provides a chemical-free solution for the harmful effects of **scale**, **corrosion**, **bacteria** and **algae** in both residential and small commercial applications. In addition, the S38 increases **filtration** efficiency via flocculation. This powerful and durable water conditioner provides a fully encapsulated printed circuit board and a power supply connection sealed with an "O" ring. The S38 fits pipes up to 38mm (1 ½") outer diameter.

The S38 device was recently awarded the prestigious 2015 Kitchen Innovations Award by the **National Restaurant Association**. This award recognizes and celebrates cutting-edge equipment and technology that specifically improves the "back of the house" operations and benefits foodservice operators.

## **Popular Applications**

- Residential and commercial plumbing systems.
- Residential and commercial water heaters.
- Commercial dishwashers.
- Steam and proofer ovens.
- Ice machines.

- Commercial humidifiers.
- Evaporators.
- Small aquariums.
- Steam rooms.

#### **Main Benefits**

- Dissolves and removes existing scale.
- Prevents new scale accumulation.
- Deactivates bacteria and algae.
- Prevents and removes biofoul.
- Boosts filtration efficiency.
- Significantly reduces corrosion.

#### **Financial and Environmental Benefits**

- Reduces energy consumption.
- Increases the efficiency of water heating equipment and machinery.
- Eliminates or decreases chemical usage.
- Decreases the need for chemical safety precautions, storage and disposal.
- Reduces maintenance costs.
- · Average one year payback period.

#### **Additional Benefits**

- Non-intrusive and easy to install no plumbing modifications required.
- Propagates the Hydropath signal along the entire water system.
- Provides 24 hour protection.
- Does not interfere with other electrical systems.

# **Specifications**

- Signal monitor light
- PSU: Input 110-240V ACUnit: Input 12V AC/DC
- Max power: 1.2 W

Weight approx: 175grams

• Dimensions: H 110 x W 67 x D 30mm

Maximum pipe diameter 38mm OD

Lead length 3m

Installation of this device does not replace periodic equipment preventative maintenance procedures.

*Hydro*FLOW residential devices are designed for ease of installation. With this said, it may be necessary to have your unit installed professionally, depending on the configuration of your plumbing system.

For additional technical information about these products, please visit our **technology**\_page. If you have any questions or wish to locate a local representative, please **contact us**.

### About *HydroFLOW* S38

The HydroFLOW S38 is the solution for hard limescale deposits in homes up to 3,000 sq. ft., commercial kitchens and steam rooms. More powerful than the HS38, the HydroFLOW S38 is designed to protect commercial heating systems, as well as appliances such as dishwashers and washing machines, and to make limescale-stained taps, sinks and surfaces easier to clean.

### บริษัท เชมมิเทค ไฮโดรเทคโนโลยี จำกัด

ที่ตั้ง : 50/12 ถนนเลียบฯฝั่งเหนือ แขวง/เขต หนองแขม

จังหวัด : กรุงเทพมหานคร

รหัสไปรษณีย์ : 10160 ประเทศ : ไทย

โทรศัพท์ : 02-450-6038 แฟกซ์ : 02-040-9132 โทรศัพท์มือถือ : 092-539-4945

Skype: maimai3963 LINE:id thaizymetec

อีเมลล์ : <u>w</u>ater@zymetec-th.com เว็บไซต์ : <u>http://www.hydroflow-th.com</u> แผนที่ : https://goo.gl/maps/irdfMn6cP6N2

หมายเลขผ้เสียภาษี :0105559025851